

Technical Data Sheet

NORTH

Product: FP722/4DP Full Body Harness



Size: Universal & XL

Colour: Shoulder straps-Blue
Leg straps -Yellow

Usage: Dorsal & Sternal D-ring Attachment for Fall Arrest
Side D-ring for Work Positioning
Front D-Ring for ladder climbing

Webbing: Polyester 1¾ inches (45 mm) wide
Tensile strength 5,000 lbs (22 kN)

Hardware: D-Ring, Quick Connects
Drop forged – alloy steel; Yellow chromate leachback & sealant
Minimum tensile strength 5,000 lbs (22 kN) for D-Ring and 4,000 (17.8 kN) for Quick Connect Buckle; D-ring 100% proof loaded to 3,600 lbs (16 kN)
D-Ring Opening Large (Dorsal & Sternal): 62 mm (2 7/16 in)
D-Ring Opening Small (Work Positioning): 44 mm (1 3/4 in)
Meets or exceeds ANSI Z-359.1 and CSA Z259.12-00 requirements

Weight: 1.2 kg (2.6 lbs)

Capacity: 310 lbs (140 kg) (combined weight of person, tools, clothing, etc)

Maximum Arresting Load: 8 kN (1,800 lbs)

Number of Workers: 1

Operating Temperature: -35 °C to +35 °C (-31°F to 95°F)

STANDARDS

Certified: CAN/CSA Z259.10 –M90 Full Body Harness Class APL

Compliance: ANSI Z359.1 and A10.14-1991 Class III OSHA 1910.66 App. C.

Component Compatibility: North full body harnesses are designed for use with North approved components or subsystems (lifelines, energy absorbers, lanyards, rope grabs and self-retracting lifelines) or as recommended by a Qualified Person.

Warnings: See Operating and Maintenance Instruction Manual for details.

Storage: Store in a cool dry place away from chemicals, water, corrosive environments, and sources of heat or spark.