DNG-250 LOW FOG GENERATOR



FEATURES

Meet Antari's latest low-lying fog technology: DNG-250. Compare to its previous version DNG-200, the DNG-250 is upgraded to a more powerful heating element and more efficient refrigeration systems, which enables it to produce higher volume and even better low fog effects.

***For best low fog effect, use Antari FLL Low Fog Fluid.**

SPECIFICATION

Rated voltage	US model : AC 100-120V, 50/60Hz EU model : AC 220-240V, 50/60Hz
Refrigerant	120V R- 404A , 1.98LB (0.8Kg) 240V R- 404A , 1.98LB (0.8Kg)
Start current	120V / 77.4A 240V / 36.1A
Rated current	120V / 14.2A 240V / 6.5A
Fog power consumption	120V / 1600W 13.5A 240V / 1600W 6.8A
Warm-up time	6 minutes (approx.)
Fluid consumption	100 ml/min
Fluid tank capacity	10 Liters (2.64 gallon)
Compatible fluid	Antari FLL Low Fog Effects Fluid
Ambient temp.range	5°C – 40°C (41°F – 104°F)
Output	120 m^2 / min
Control Methods	Manual, Timer, DMX 512
DMX channels	2 channels
Interface	Neutrik Powercon (Power) XLR 3-pin and 5-pin (DMX)
Optional Accessories	FDNG-250 Flight Case、 FTA-200 Fog Conducting Hose Adaptor、 C0DNG0600 3 Meter Fog Confucting Hose
Dimension	L 780 W 608 H 715 mm (L 30.7 W 23.93 H 28.15 inch)
Weight	130 kg (286.6 lbs)







EFFECTS



ACCESSORIES



OPTIONAL FDNG-250 Flight Case

FLUIDS



FLL-10 Log Fog Effects Fluid

SUPPORT

DNG-250 User Manual
1 file(s) 2.01 MB
DOWNLOAD

NEED HELP ? THERE ARE SEVERAL WAYS TO GET THE SUPPORT YOU NEED

WHERE TO BUY? | SERVICE AND REPAIR | MAIL US

ANTARI LIGHTING & EFFECTS LTD. | VAT NUMBER : 86341610 | 8, LANE 231, SEC. 1, NANKAN RD., LUCHU, TAOYUAN, TAIWAN. COPYRIGHT © 2023 ANTARI LIGHTING & EFFECTS LTD. ALL RIGHTS RESERVED.