Hushida D2-Pro Interactive Whiteboard Parameters Sheet

Display	Model	XSKB-65	XSKB-75	XSKB-86
	Attributes	65"	75"	86"
	Backlight Type	D-LED		
	Panel Type	ADS		
	Display Area	1428.48(H)×803.52 (V)mm	1649.7(H)×927.9(V) mm	1895.04(H)×1065.96 (V)mm
	Resolution	3840×2160 4K FHD/4K UHD		
	Pixel Gap	0.372*0.372mm	0.4296*0.4296mm	0.4935*0.4935mm
	Chroma	1.07B（10bit）		
	Brightness	350cd/m²		
	Reponse Time	8ms		
	Ratio contrast	1200:1`		
	Color gamut	72%	72%	68%
	Visible Angle	178°(H/V）		
	Life time	>30000H		
Android System (Optional)	Chips	TP.T982		
	CPU	Four-core A55		
	GPU	Mali- G52MP2		
	System	Android 11.0		
	Memory	4G+32G		
	Interface	HDMI IN、USB2.0、USB3.0、AUDIO IN、AUDIO OUT、SPDIF、RJ45 IN、RJ45 OUT、VGA IN、RS232、TOUCH OUT2.0		
Windows System (Optinal)	Chips	Intel		
	CPU	OPS-8, i5/i7(optional)		
	Running Memory	8G DDR4（optional）		
	HardDisk	256G SSD（optional）		
	Interface	Power、LAN、USB2.0、USB3.0、HDMI、TYPE-C、Microphone、Earphone		
Accessories	Camera	In-builing 1300 million pixels		
	MicroPhone	Quantities 6 / Distance 0~8m		
	Audio	2*10W		

Touch	Touch	Infrared Frame		
	Touch Points	20		
	Reponse Time	≤15ms		
	Precision	At least 90% area +-2mm		
Physical Parameters	Weight	Net weight：34kg Gross Weight：43.75 kg	Net Weight：46kg Gross Weight：59.55 kg	Net Weight：60kg Gross Weight：75.7 kg
	Size(L*W*T)	1488(L)*906(W)*87 (T)mm	1709(L)*1029(W)*88 (T)mm	1957(L)*1109(W)*88 (T)mm
	Package Size (L*W*T)	1610(L)*1020(W) *200(T)mm	1890(L)*1220(W) *200(T)mm	2120(L)*1350(W) *240(T)mm
	Enclosure Material	Aluminum Alloy/Sheet Metal		
	Enclosure Color	Black/Grey		
	Wall mounting hole distance	600*400mm	800*400mm	800*600mm
	Screw Size	8*25mm	8*25mm	8*25mm
	Power	AC100-240V~(+/-10%),50/60Hz		
	Power Consumption	181.1W	158W	--
	Working Temperature	0°C ～ 40°C		
	Stocking Temperature	-20°C ～ 60°C		
Certification	Attachments	User manual, warranty card, certificate of conformity, WIFI, set of Wall bracket+screws		
	Certification	CCC，CECP，CE，ROHS，FCC		

Copy rights·2022 · Guang Dong Hushida Electronic Technology Co.,Ltd | All rights reserved