天津市新宇彩板有限公司
TIANJIN XINYU COLOR PLATE Co., Ltd

产品质量证明书
QUALITY CERTIFICATE

中国天津西青区南河工业园邮编：300382
Nanhe Industrial park, Xiqing
District, 300382, Tianjin,P.R. China
TEL:400-630-8518 FAX:022-23811448

客户名称 Customer	GYJ FERRETERIAS SA	证书编号 Certificate No.	2305088	签发日期 Date of Issue	2023. 05. 08
		合同号 Contract No.	FGQXE230328JUAN-GYJ		
产品名称 Product	热浸镀锌钢卷 HOT-DIP GALVANIZED STEEL COILS	产品标准 Specification	ASTM A653-94		

钢卷号 Coil No.	规格及重量 Material			化学成分 Chemical Composition%						拉伸测试 Tensile Test			锌层重量	锌花	硬度	表面级别	弯曲性能	表面处理
	厚度 Thick	宽度 Width	重量 Mass	C	Si	Mn	P	S	B	屈服强度	抗拉强度	延伸率	Coating Mass	Spangle	HRB	Surface	Bend	Surface Treatment
	mm	mm	t							Y.S MPa	T.S MPa	EL%	g/s'					
JP326951F0D3HH00S	1.85	1220	6.972	0.045	0.120	0.22	0.018	0.013	≥0.0008	295	389	36	180	一般	60	FA	OK	C
JP326952F0D1HH00S	1.45	1220	6.954	0.045	0.120	0.22	0.018	0.013	≥0.0008	320	388	32	180	一般	61	FA	OK	C
JP326952F0D2HH00S	1.45	1220	6.952	0.045	0.120	0.22	0.018	0.013	≥0.0008	320	388	32	180	一般	61	FA	OK	C
JP326952F0D3HH00S	1.45	1220	7.292	0.045	0.120	0.22	0.018	0.013	≥0.0008	320	388	32	180	一般	61	FA	OK	C
JP326954F0D1HH00S	1.45	1220	6.936	0.045	0.120	0.22	0.018	0.013	≥0.0008	332	398	32	180	一般	61	FA	OK	C
JP326954F0D2HH00S	1.45	1220	6.936	0.045	0.120	0.22	0.018	0.013	≥0.0008	332	398	32	180	一般	61	FA	OK	C
JP326954F0D3HH00S	1.45	1220	6.578	0.045	0.120	0.22	0.018	0.013	≥0.0008	332	398	32	180	一般	61	FA	OK	C
JP326955F0D1HH00S	1.45	1220	6.926	0.045	0.120	0.22	0.018	0.013	≥0.0008	323	394	34	180	一般	59	FA	OK	C
JP326955F0D2HH00S	1.45	1220	6.926	0.045	0.120	0.22	0.018	0.013	≥0.0008	323	394	34	180	一般	59	FA	OK	C
JP326955F0D3HH00S	1.45	1220	7.38	0.045	0.120	0.22	0.018	0.013	≥0.0008	323	394	34	180	一般	59	FA	OK	C
JP326957F0D1HH00S	1.15	1220	7.032	0.045	0.120	0.22	0.018	0.013	≥0.0008	331	398	36	180	一般	62	FA	OK	C
JP326957F0D2HH00S	1.15	1220	7.024	0.045	0.120	0.22	0.018	0.013	≥0.0008	331	398	36	180	一般	62	FA	OK	C
JP326957F0D3HH00S	1.15	1220	7.236	0.045	0.120	0.22	0.018	0.013	≥0.0008	331	398	36	180	一般	62	FA	OK	C
JP326958F0D1HH00S	1.15	1220	7.046	0.045	0.120	0.22	0.018	0.013	≥0.0008	326	389	32	180	一般	63	FA	OK	C
JP326958F0D2HH00S	1.15	1220	7.042	0.045	0.120	0.22	0.018	0.013	≥0.0008	326	389	32	180	一般	63	FA	OK	C
合计 Total			105.232															
备注 Remarks	Boron Added																	

结论 Conclusion	本产品已按上述标准要求制造和检验，其结果符合要求，特此证明。 We hereby certify that material described herein has been manufactured and tested with satisfactory results in accordance with the requirements of the above material specification.

质量证明专用章
Stamp