Oil Free Vacuum Pump

VIDEO

2 YEAR WARRANTY

Features

- **No air pollution, maintenance free**
  Rocker series pumps are driven by piston, without the need of lubricant, regular oil changes and maintenance; with no oil pollution.
- **Prote™ overflow protection**
  Rocker series pumps are equipped with Prote™ overflow protection which can prevent a large amount of liquid from being sucked into the pump.
- **Moisture trap with filter cartridge**
  Rocker series pumps are equipped with filter cartridge at the air inlet to filter particle and moisture to prolong the life of pump.
- **Vacuum regulator**
  Rocker series pumps are equipped with vacuum regulator to adjust vacuum.
- **Thermal protection device**
  Every motor of Rocker series pumps has a built-in thermal protection device to shut off the pump automatically when overheated and then resume working when the temperature cools down.
- **International certification**
  CE certication
  CSA certication
  IP 30 protection
  RoHS certication
- **Two-Year Warranty**

Applications

- Suspended solid test
- Vacuum filtration
- Microbiological test
- Air sampling


Ordering Information

167400-11(22)
Rocker 400, Vacuum Pump
AC110V, 60Hz (AC220V, 50Hz)

167410-11(22)
Rocker 410, Vacuum Pump
AC110V, 60Hz (AC220V, 50Hz)

Patent : M491731





Prote™ overflow protection

Rocker 400



Rocker 410

Specification

Model	Rocker 400		Rocker 410	
Voltage / Freq.	110V/60Hz	220V/50Hz	110V/60Hz	220V/50Hz
Max. power	100W	80W	100W	80W
Max. current	1.0A	0.4A	1.0A	0.4A
Max. vacuum	105 mbar		30 mbar	
Max. flow rate	37 L/min	34 L/min	23 L/min	20 L/min
Motor rotation speed	1750 RPM	1450 RPM	1750 RPM	1450 RPM
Horse power	1/6 HP		1/6 HP	
Noise level	52 dB		52 dB	
Hose barb	ID8		ID8	
Vacuum regulator	Yes		Yes	
Overflow protection/ Filter cartridge	Yes		Yes	
Safety	Thermal Protection		Thermal Protection	
Net weight	5.2 Kg		5.2 Kg	
Dimension (LxWxH)	31 x 13.5 x 20.4 cm		31 x 13.5 x 20.4 cm	