UL Product iQ®

Audible-signal Appliances

COMPANY

System Sensor Unincorporated, Div of Honeywell International Inc
3825 Ohio Ave
Saint Charles, IL 60174-5467 United States

S4011

Bells, vibrating, Models SSM24-6, SSM24-8, SSM24-10, SSV120-6, SSV120-8, SSV120-10 for outdoor use when used with NEMA 3R weather resistant back box, Model WBB.

Chimes, Model CH12/24 for indoor use private mode only; Model WBB for outdoor use.

Models CHR, CHW, CHRA, CHWA. For indoor use, private mode use only.

Chimes/strobes, Models CH24MC, CH24MCW. For wall mount, indoor use.

Models CHSR, CHSW. For indoor use only, private mode use only.

Horns, Model PA400W with or without suffix -F. For indoor use only.

Models HR, HW. Intended for indoor use mounted on the wall or ceiling.

Models MHR, MHW. For indoor use only.

Tones 1, 2, 3 and 4 are Public Mode at 24V DC/FWR.

Tone 3 is Public Mode at 12V DC.

Tones 1, 2 and 4 are Private Mode at 12V DC.

Tones 1, 2, 3 and 4 are Private Mode at 12V FWR.

Model APA151. For indoor use only. Public mode.

Mini-Horn, Model MHR1, Input: 8 - 33 Vdc, 8 - 33 Vfwr; for indoor use only.

Sounder/strobes, Model P2475RL . May employ "W" or "Z" suffix. For indoor wall mount only.

Model P12015K for indoor or outdoor use.

Directional sounders, Model PF24V for supplemental fire alarm use. Indoor use only.

520 Hz Low frequency sounders, Models HR-LF, HW-LF. Intended for indoor use only and may be mounted on the wall or the ceiling.

520 Hz Low frequency sounders/strobes, Models P2RH-LF, P2WH-LF. Intended for indoor use only and may be mounted on the wall or the ceiling.

SPECTRALERT ADVANCE SERIES HORNS, CHIMES AND COMBOS

***General** - Models with "K" in the suffix are suitable for indoor or outdoor use with an operating temperature rating of -40°C to +66°C (-40°F to +151°F) and have a NEMA Type 3, 3R and 4X enclosure ratings only when used with the Listed Plastic models SA-WBB and SA-WBBW (wall) or the Plastic models SA-WBBC and SA-WBBCW (ceiling) weatherproof back boxes. Models with "-P" in the suffix have plain housings with no lettering on the enclosure. Models not containing either "-P", in the suffix have English lettering reading "FIRE" on the housing. Models with the "-SP" suffix have Spanish lettering reading "FUEGO" on the housing. Models with the "-PG" suffix have Portuguese lettering reading "FOGO" on the housing.

Horns - Models HR, HW. Intended for indoor use mounted on the wall or ceiling, Models HRK, and HWK, intended for indoor or outdoor use, mounted on the wall or ceiling. *

Horns, Models HWL-LF(a), HRL-LF(a), HGWL-LF(a), HGRL-LF(a) Intended for indoor use mounted on the wall.

Horns, Models HCWL-LF(a), HCRL-LF(a) Intended for indoor use mounted on the ceiling.

Chimes - Models CHR, CHW are intended for private mode only. Intended for indoor use mounted on the wall or ceiling.

Chime/Strobes - Models CHSR, CHSW are intended for private mode only. Intended for indoor use mounted on the wall or ceiling.

Horn/Strobes - Two-wire type, rectangular enclosure, Models P2R, P2W, P2RH, P2WH. Intended for indoor use mounted on the wall or ceiling, Models P2RK, P2RK-R, P2RK-P, P2WK, P2WK-R, P2WK-P, P2RHK, P2RHK-R, P2RHK-P, P2WHK, P2WHK-R, P2WHK-P, intended for indoor and outdoor use, mounted on the wall or ceiling *.

Horn/Strobes - Two-wire type, round enclosure, Models PC2R, PC2W, PC2RH, PC2WH. Intended for indoor use mounted on the wall or ceiling, Models PC2RK, PC2RK-R, PC2RK-P, PC2WK, PC2WK-R, PC2WK-P, PC2RHK, PC2RHK-R, PC2RHK-P, PC2WHK, PC2WHK-R, PC2WHK-P, intended for indoor and outdoor use, mounted on the wall or ceiling *.

Horn/Strobes, Two-wire type, rectangular enclosure, Models P2WL-LF(a) and P2RL-LF(a) Intended for indoor use mounted on the wall. Round enclosure , Models PC2RL-LF and PC2WL-LF intended for indoor use mounted on the ceiling.

Horn/Strobes - Four-wire type, rectangular enclosure, Models P4R, P4W, P4RH, P4WH. Intended for indoor use mounted on the wall or ceiling, Models P4RK, P4WK, P4RHK and P4WHK, intended for outdoor use, mounted on the wall or ceiling *.

Horn/Strobes - Four-wire type, round enclosure, Models PC4R, PC4W, PC4RH, PC4WH. Intended for indoor use mounted on the wall or ceiling, Models PC4RK, PC4WK, PC4RHK, P4WHK-P and PC4WHK, intended for outdoor use, mounted on the wall or ceiling *.

GLOBAL AV COMBO PRODUCT SERIES HORNS, STROBES AND COMBOS:

General - Models for indoor wall and ceiling mount only and for use with an operating temperature of 0°C to +49°C (32°F to +120°F). Models with "R" in the suffix implement a red strobe lens.

Horn/Strobes - Two-wire type, rectangular enclosure, Models SYS-HS, SYS-HSR, SYS-HSR-FIRE, SYS-HSW, SYS-HSRW, SYS-HSRW-FIRE. Intended for indoor use mounted on the wall or ceiling.

Accessories:

Back box, Model WBBF for indoor/outdoor use.

Models SA-WBB, SA-WBBC (Back boxes for Spectralert Advance Series) for indoor/outdoor use.

Weatherproof plates, Models WTP, WTPW, WTP-SP, WTP-SPW, with a NEMA Type 3R and IP22 enclosure ratings. May be used in place of the listed weatherproof back boxes as follows:

Models WTP (Red), WTPW (White) Weatherproof Plates used with horn and horn/strobes models with "K" suffix, suitable for indoor or outdoor flush mount usage, wall or ceiling, with an extended operating temperature range of -40 degrees F to 151 degrees F (-40 degrees C to 66 degrees C). They can be mounted to 2 inch by 4 inch or 4 inch by 4 inch back boxes, with a 1-1/2 inch minimum depth.

Models WTP-SP (Red), WTP-SPW (White) Weatherproof Plates used with speakers and speaker/strobes models with "K" suffix, suitable for indoor or outdoor use flush mount usage, wall or ceiling, with an operating temperature rating of -40 degrees F to 151 degrees F (-40 degrees C to 66 degrees C). They can only be mounted to a 4 inch by 4 inch by 2-1/8 inch back box.

Sync modules, Models MDL3R, MDL3W, MDL, MDLW.

Models MDL3R, MDL3W are also Listed under Audible-signal Appliances (ULSZ).

120 VAC adapter mounting plate, Model MP120K may be used with Models P2R, P2RH, P2RK, P2RHK, P2W, P2WH, SR, SRH, SRK, SRHK, SW, SWH, PC2R, PC2RH, PC2RK, PC2RHK, PC2W, PC2WH, SCR, SCRH, SCRK, SCRHK, SCW, SCWH, HR, HRK, HW, SR-P, SW-P, SRH-P, SWH-P, P2R-P, P2W-P, P2RH-P, P2WH-P, SCR-P, SCW-P, SCRH-P, SCWH-P, PC2R-P, PC2W-P, PC2RH-P, PC2WH-P, SR-SP, SRH-SP, P2R-SP, P2RH-SP, SCW-SP, SCWH-SP, PC2W-SP, PC2WH-SP, CHR, CHW, CHSR, CHSW.

Smoke detector audible bases, Models B501BH, B501BHT, B501BH-2, B501BHT-2.

Wireless AV Base, Ceiling, Models WAV-CRL and WAV-CWL (***); and Wall, Models WAV-RL and WA-WL (***) .

Audible signal appliance accessories, accessory retrofit trim plates, Models RFP, RFPW. Optional with Series H horns, Series CH Chimes, Series CHS Chime/Strobes, Series P2 Horn/Strobes, Series PC2 Horn/Strobes, Series P4 Horn/Strobes, and Series PC4 Horn/Strobes.

Audible signal appliance accessories, accessory trim rings, Models TR-HS, TRW-HS, TRC-HS, TRCW-HS. Optional with Series H horns, Series CH Chimes, Series CHS Chime/Strobes, Series P2 Horn/Strobes, Series PC2 Horn/Strobes, Series P4 Horn/Strobes, and Series PC4 Horn/Strobes.

Ceiling trim ring, Optional with Models SYS-HS, SYS-HSR, SYS-HSR-FIRE, SYS-ST, SYS-STR.

Ceiling trim plates, Models SYS-CTP, SYS-CTPR, SYS-CTPR-FIRE, SYS-CTPW, SYS-CTPRW, SYS-CTPRW-FIRE.

Horns*, Models HWL**, HRL**, HGRL**, HGWL**.

Chimes*, Models CHWL**, CHRL**.

Horn Strobes*, Models P2RL, P4RL, P2WL, P4WL, P2GRL, P2GWL, P2RL-P, P2WL-P, P2RL-SP, P2WL-SP, PC2RL, PC4RL, PC2WL, PC4WL.

Chime Strobes*, Models CHSRL, CHSWL, CHSCRL, CHSCWL.

Horn Strobes, Models P2RLED, P2WLED, P2RLED-B, P2RLED-B, P2RLED-P, P2WLED-P, P2RLED-SP, P2WLED-SP, PC2RLED, PC2WLED, PC2RLED-B, PC2WLED-B, P2GRLED, P2GWLED, P2GRLED-B, P2GWLED-B

Horns (**) (b) (c), Models HGRKL, HGRKL-B.

Horn Strobes (b) (c), Models P2GRKLED, P2GRKLED-P, P2GRKLED-B, P2GWKLED, P2GWKLED-P, P2GWKLED-B. Intended for Wall Mount.

Horn Strobes (b) (c), Models PC2RKLED, PC2RKLED-P, PC2RKLED-B, PC2WKLED, PC2WKLED-P, PC2WKLED-B. Intended for Ceiling Mount.

Chime/Strobes - Models CHSRLED, CHSRLED-B, CHSWLED, CHSWLED-B are intended for private mode only. Intended for indoor use mounted on the wall.

Chime/Strobes - Models CHSCRLED, CHSCRLED-B, CHSCWLED, CHSCWLED-B are intended for private mode only. Intended for indoor use mounted on the Ceiling.

(*) May be used with accessory models; TR-2, TR-2W, TRC-2, and TRC-2W, installed on compatible enclosure models SBBRL, SBBWL, SBBGRL, SBBGWL, SBBCRL, and SBBCWL, and used with AC adapter mounting plate models MP120KL & MP120KLA.

(**) Suitable for use on wall & ceiling.

(***) Compatible only with Listed Models PC2RL, PC2WL, P2RL, P2WL, P2WL-P, P2WL-SP, P2RL-P, P2RL-SP, CHSCRL, CHRL, CHWL, CHSCWL, CHSRL, CHSWL, HRL, HWL, HRL-LF, HWL-LF, P2RL-LF, P2WL-LF, HCRL-LF, HCWL-LF, HGRL-LF, HGWL-LF, CHSCRL, CHSCWL, PC2RL, PC2WL.

(a) Devices may be bulk-packed with System Sensor added internal control number suffix -BP10 on master shipping carton.

(b) Intended for outdoor wet use.

(c) Rated Type 4X and IP56 as standalone devices (without the backbox).

Last Updated on 2024-09-16

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2024 UL LLC."