

YOUR WORLDWIDE PARTNER IN THE LABORATORY

CATALOGUE 2024 – 2026

BOECO Germany



BOECO WS 4000 / WS 8000

Stainless steel water still with thermostatic low water cut-off and level switch which activates the heater if there is enough level of water in the boiler.

Specification:	**WS 4000**	**WS 8000**
Distillate flow rate:	approx. 4 l/h	approx. 7,5-8 l/h
Cond. of dist water (20°C):	approx. 1,5 µS/cm	
Heater:	3 KW	6 KW
Cooling water:	approx. 60 l/h	approx. 84 l/h
Material: Inner part:	Stainless steel	
Outer part:	Stainless steel & powder coating	
Size: (h x w x d)	435x370x220mm	635x370x260 mm
Switch:	Main power with pilot lamp	
Sealing:	Silicone gasket	
Safety:	Low water level & over heating cut-off	
Weight:	8,6 kg	12,2 kg

Code	Description
BOE 8703600	WS 4000, 230 V
BOE 8703601	WS 4000, 110 V
BOE 8707500	WS 8000, 230 V



BOECO WS 4000 / WS 8000

BOECO WS 12000

Stainless steel water still with thermostatic low water cut-off and level switch which activates the heater if there is enough level of water in the boiler.

Specification:	**WS 12000**
Distillate flow rate:	12 l/h
Conductivity:	2,0 µS/cm
Electricity consumption:	7800 W
Cooling water:	approx. 1,6 l/min
pH	5,5-7
Material: Inner part:	Stainless steel
Outer part:	Stainless steel & powder coating
Size: (h x w x d)	670 x 370 x 260 mm
Weight:	13,0 kg

Code	Description
BOE 8712000	WS 12000, 380 V



BOECO WS 12000

BOECO DEST TANK 4000 / 8000

Stainless steel water still for automatic and continuous operation with built-in 8/16 l storage tank. For bench and wall mounting. Supplied with wall mounting bracket. Excellent quality of distillation. An electronic level switch switches the still off when the storage tank is full and restarts it automatically when destilled water is withdrawn. Dispenser Tap of distilled water.
With flow regulator to avoid excessive water consumption.

Specification:	**DEST TANK 4000**	**DEST TANK 8000**
Distillate flow rate:	approx. 4 l/h	approx. 8 l/h
Water tank capacity:	8 l	16 l
Cond. of dist water (20°C):	approx 1,5 µS/cm	
Power:	3.000 W	6.000 W
Cooling water:	approx. 55 l/h	approx. 80 l/h
Material: Inner part:	Stainless steel	
Outer part:	Galvanized steel & powder coating	
Switch:	Main power with pilot lamp	
Safety:	Low water level & over heating cut-off	
Size (wxdxh):	620x330x460 mm	720x350x700 mm
Weight:	24,6 kg	36,0 kg

Code	Description
BOE 8704500	DEST TANK 4000, 230 V
BOE 8704501	DEST TANK 4000, 115 V
BOE 8708000	DEST TANK 8000, 230 V



BOECO DEST TANK 4000 / 8000