Under counter Pharmacy refrigerator

Midea | Biomedical

Suitable to store vaccines, medicines and laboratory products at 2℃ to 8℃ temperature range.
Application could be found at pharmacies, pharmaceutical factories, hospitals, CDC, clinics laboratories.
Leading technologies for Safer storage and Higher temperature stability.



MC-5L126

Safe storage


Microcomputer control;
Temperature accuracy 0.1℃;
Temperature Uniformity +/- 1.5 ℃;
Audible & visual alarm systems;
Remote alarm contact;
CFC free, environment friendly;
High quality coated steel chamber.

Reliable & Stable performance

International famous compressor;
Built-in Air duct;
DC turbo Fan;
Patented D+ heat exchange technology;
LBA forming technology.


Humanized Design, User Friendly

LED light;
Safety lock;
door self-lock;
Grip handle;
Reversible door;
Adjustable shelves, label holder;
Porthole;
Wide voltage range.



DC Turbo Fan

IDecrease noise level by 8% Integrated DC Turbo Fan works with smaller vibration and higher efficiency.
Safer for daily use No strong electric component in chamber, safer & more reliable.



Built-in air duct

Increase the effective interior space by 10% Less interior space occupancy.
Built-in air duct plus the Top cooling design, ensure temperature in the top of chamber is cool enough for storage.

Midea | Biomedical

Under counter Pharmacy refrigerator

LED Display


Display real-time temperature




LBA Forming Technology

The world's leading fourth generation foaming agent
More uniform density, Better insulation, more energy-saving.
More reasonable foaming layer design, larger interior storage space.

Typical Performance Characteristics at 25℃ Ambient





Item	Model No.	MC-5L126
Dimensions	Load capacity (40HQ)	162
	Fridge Storage Volume(L)	126
	Product Dimensions(mm)(wxdxh)	595*615*810
	Interior Dimensions(mm)(wxdxh)	505*467*620
	Net/Gross Weight	43/48
Technical data	Cooling Type	Forced air cooling
	Defrost type	No frost
	Climate Class	N
	Refrigerant/Amount(g)	R600a/26g
	Compressor type	Fixed frequency
	Power supply	220~240V/ 50Hz
Product Performance	Temperature Range	2 ~ 8℃
	Temperature uniformity/°C	±1
	Temperature volatility/°C	2
	Temperature Accuracy	0.1
Control	Controller	Microprocessor
	Display	LED
Alarms	Power Failure Alarm	Y
	Sensor Failure Alarm	Y
	Ambient Temperature Alarm	N
	Door ajar Alarm	Y
	High Temperature Alarm	Y
	Low Temperature Alarm	Y
	Remote Alarm	Y
Accessorie	Shelves Qty	3
	Anti-condensation Door	LOW-E glass
	Door Self-lock	Y
	Reversible door	Y
	Cable Port	1
	USB	Optional
	Remote Alarm	Y
	RS485 port	N
	Printer	Optional
	Backup Battery	Y
	Backup Battery endurance	24h

Midea Biomedical Co.,Ltd. Global integrated cold chain solutions supplier

+86-551-62213025 http://www.midea.com/global/

Midea Refrigerator Industrial Zone, Zishi Road, Economic & Technological Zone,Hefei, China