# CERTIFICATE OF COMPLIANCE

| | |
|---|---|
| **Certificate Number** | 20180913-MH28329 |
| **Report Reference** | MH28329-20170525 |
| **Issue Date** | 2018-SEPTEMBER-13 |
| **Issued to:** | STERLING ROPE CO. INC.<br>26 Morin Street<br>Biddeford, ME 04005-4413 |
| **This is to certify that representative samples of** | Life Safety Rope and Equipment for Emergency Services and Single Anchor Lifelines<br>See Next Page for Models<br><br>Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate. |
| **Standard(s) for Safety:** | NFPA 1983, Standard on Life Safety Rope and Equipment for Emergency Services, 2017 Edition<br>ANSI/ASSE Z359.15, Safety Requirements for Single Anchor Lifelines and Fall Arresters for Personal Fall Arrest Systems, 2014 Edition |
| **Additional Information:** | See the UL Online Certifications Directory at www.ul.com/database for additional information |

Only those products bearing the UL Certification Mark should be considered as being covered by UL's Certification and Follow-Up Service.

Look for the UL Certification Mark on the product.

Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at http://ul.com/aboutul/locations/

# CERTIFICATE OF COMPLIANCE

**Certificate Number** 20180913-MH28329
**Report Reference** MH28329-20170525
**Issue Date** 2018-SEPTEMBER-13

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Life Safety Ropes and Single Anchor Lifelines:

| Model Number | Designation | Diameter (mm) | Use Class | MBS (kN) | Percent Elongation (%) | | ANSI/ASSE? |
|---|---|---|---|---|---|---|---|
| P1600XXXXX | 5/8" HTP | 16.0 | General | 57.8 | @ 1.35 kN | 1.6 | Z359.15 |
| | | | | | @ 2.7 kN | 2.1 | |
| | | | | | @ 4.4 kN | 2.5 | |
| | | | | | @ 1800 lbf | 2.5 | |
| SS155XXXXXX | 5/8" SuperStatic2 | 16.0 | General | 55.0 | @ 1.35 kN | 1.4 | No |
| | | | | | @ 2.7 kN | 3.4 | |
| | | | | | @ 4.4 kN | 5.0 | |
| P1300A0xxx | ½" (13mm) HTP | 13.0 | General | 41.6 | @ 1.35 kN | 0.8 | No |
| | | | | | @ 2.7 kN | 1.5 | |
| | | | | | @ 4.4 kN | 2.0 | |
| P1300XXXXX<br>WF-PSK125xxxxxx | ½" HTP | 12.5 | General | 40.4 | @ 1.35 kN | 1.0 | Z359.15 |
| | | | | | @ 2.7 kN | 1.6 | |
| | | | | | @ 4.4 kN | 2.0 | |
| | | | | | @ 1800 lbf | 3.5 | |
| SS125XXXXXX | ½" SuperStatic2 | 12.5 | General | 41.1 | @ 1.35 kN | 1.5 | Z359.15 |
| | | | | | @ 2.7 kN | 3.6 | |
| | | | | | @ 4.4 kN | 6.0 | |
| | | | | | @ 1800 lbf | 9.6 | |
| SS1254000XX | ½" SuperStatic2<br>Safety Glo | 12.5 | General | 41.1 | @ 1.35 kN | 1.5 | No |
| | | | | | @ 2.7 kN | 3.6 | |
| | | | | | @ 4.4 kN | 6.0 | |
| T12DBAAxxx | ½" H3 Tech125 | 12.5 | General | 42.0 | @ 1.35 kN | 1.0 | No |
| | | | | | @ 2.7 kN | 1.4 | |
| | | | | | @ 4.4 kN | 1.8 | |
| WP1250x0xxx | 12.5mm WorkPro | 12.5 | General | 45 | @ 1.35 kN | 2.5 | No |
| | | | | | @ 2.7 kN | 4.6 | |
| | | | | | @ 4.4 kN | 7.4 | |
| T11ANXXX | Tech 11 | 11.0 | General | 40.1 | @ 1.35 kN | 3.4 | No |
| | | | | | @ 2.7 kN | 5.5 | |
| | | | | | @ 4.4 kN | 8.3 | |

Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at http://ul.com/aboutul/locations/

# CERTIFICATE OF COMPLIANCE

**Certificate Number** 20180913-MH28329
**Report Reference** MH28329-20170525
**Issue Date** 2018-SEPTEMBER-13

Life Safety Ropes and Single Anchor Lifelines cont'd:

| Model Number | Designation | Diameter (mm) | Use Class | MBS (kN) | Percent Elongation (%) | | ANSI/ASSE ? |
|---|---|---|---|---|---|---|---|
| WP110XXXXXX | 11mm WorkPro | 11.0 | Technical | 36.0 | @ 1.35 kN | 3.5 | No |
| | | | | | @ 2.7 kN | 6.2 | |
| | | | | | @ 4.4 kN | 9.3 | |
| P110XXXXXX | 7/16" HTP | 11.0 | Technical | 30.5 | @ 1.35 kN | 1.9 | Z359.15 |
| | | | | | @ 2.7 kN | 3.1 | |
| | | | | | @ 4.4 kN | 3.7 | |
| | | | | | @ 1800 lbf | 5.7 | |
| SS110XXXXXX | 7/16" SuperStatic2 | 11.0 | Technical | 29.0 | @ 1.35 kN | 3.2 | No |
| | | | | | @ 2.7 kN | 5.7 | |
| | | | | | @ 4.4 kN | 8.5 | |
| WF-PSK110XXWIP | 7/16" Westfall PSK | 11.0 | Technical | 30.5 | @ 1.35 kN | 1.7 | Z359.15 |
| | | | | | @ 2.7 kN | 2.4 | |
| | | | | | @ 4.4 kN | 3.3 | |
| | | | | | @ 1800 lbf | 4.7 | |
| P106XX0XXX | 10.5 mm HTP | 10.5 | Technical | 26 | @ 1.35 kN | 1.7 | No |
| | | | | | @ 2.7 kN | 2.4 | |
| | | | | | @ 4.4 kN | 3.4 | |
| WP1000x0xxx | 10mm WorkPro | 10.0 | Technical | 29.0 | @ 1.35 kN | 3.5 | No |
| | | | | | @ 2.7 kN | 7.4 | |
| | | | | | @ 4.4 kN | 10.0 | |
| P105XXXXXX | 3/8" HTP | 10.0 | Technical | 26.6 | @ 1.35 kN | 1.4 | No |
| | | | | | @ 2.7 kN | 2.1 | |
| | | | | | @ 4.4 kN | 3.1 | |
| SS095XXXXXX | 3/8" SuperStatic2 | 9.5 | Technical | 22 | @ 1.35 kN | 3.3 | No |
| | | | | | @ 2.7 kN | 6.5 | |
| | | | | | @ 4.4 kN | 9.2 | |
| F095ANXXX | Tactical Response | 9.5 | Technical | 30.0 | @ 1.35 kN | 3.4 | No |
| | | | | | @ 2.7 kN | 6.2 | |
| | | | | | @ 4.4 kN | 8.8 | |

Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at http://ul.com/aboutul/locations/

# CERTIFICATE OF COMPLIANCE

**Certificate Number** 20180913-MH28329
**Report Reference** MH28329-20170525
**Issue Date** 2018-SEPTEMBER-13

Fire Escape Ropes:

| Model Number | Rope Designation | Diameter (mm) | MBS (kN) | Percent Elongation (%) | |
|---|---|---|---|---|---|
| F075ANXXXX | EscapeTech | 7.5 | 17.4 | @ 1.35 kN | 5.8 |
| | | | | @ 2.7 kN | 7.7 |
| | | | | @ 4.4 kN | 9.7 |
| F075AAXXXX<br>F1011XXXX | FireTech | 7.5 | 25.5 | @ 1.35 kN | 0.8 |
| | | | | @ 2.7 kN | 1.4 |
| | | | | @ 4.4 kN | 1.8 |
| F075ANR0xx<br>F075ASC0xxx<br>F075ASCH0xx | TSafe | 7.5 | 17.9 | @ 1.35 kN | 5.9 |
| | | | | @ 2.7 kN | 9.0 |
| | | | | @ 4.4 kN | 11.6 |
| F075AA2XXXX | FireTech2 | 7.5 | 25.5 | @ 1.35 kN | 1.6 |
| | | | | @ 2.7 kN | 2.0 |
| | | | | @ 4.4 kN | 2.3 |
| F077ANXXXX<br>F1011XXXX<br>F1012XXXX | SafeTech | 8.0 | 19.5 | @ 1.35 kN | 6.3 |
| | | | | @ 2.7 kN | 9.6 |
| | | | | @ 4.4 kN | 12.0 |

Escape Ropes:

| Model Number | Rope Designation | Diameter (mm) | MBS (kN) | Percent Elongation (%) | |
|---|---|---|---|---|---|
| PER080XXXXXX | 8mm PER | 8.0 | 15.5 | @ 1.35 kN | 7.4 |
| | | | | @ 2.7 kN | 11.7 |
| | | | | @ 4.4 kN | 15.6 |

Throwlines:

| Model Number | Rope Designation | Diameter (mm) | MBS (kN) |
|---|---|---|---|
| W0950XXXXX | 3/8” Waterline | 9.5 | 15.2 |
| G09509XXXX | 3/8” Grabline | 9.5 | 14.6 |

The ‘X’ in model number is replaced by letters to indicate color and by numbers to indicate length in meters in package.

Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at http://ul.com/aboutul/locations/