CMC PROSWIVEL™ PULLEYS



CMC ProSwivel Pulleys are all certified to NFPA standards. Please note we are currently phasing-in dual certified pulleys that are classified to both NFPA and EN standards. As these parts become available, we will update the product photos and the certification table below. Please contact Customer Support if you have any questions.

CMC ProSwivel Pulleys combine a swivel and pulley into a single device with a moving sideplate that allows rope loading/unloading while attached to the anchor. Available in sheave sizes from 1.1″ radius up to 2.6″, these pulleys are an excellent option for mechanical advantage systems for hauling and ascending, and they work well in combination with high anchors, tripods, and redirects.

Teaming up with Rock Exotica, CMC now offers more swivel pulleys certified to NFPA and EN standards. Our expanded ProSwivel line includes eight pulleys to choose from. Select the best ProSwivel Pulley for the job, going bigger for more efficiency or smaller when weight is critical. For more swivel pulley options, check out our single and double SWIVO™.

Expanding on the original, patented swivel pulley line by Rock Exotica, the CMC ProSwivel Pulleys are time-tested, made in the USA, and brought to you by two companies committed to quality and service.

New Additions:

- 2.0″ PMP Single Pulley – G-Rated, prusik minding, and up to 3% more efficient than 1.5″
- 2.0″ PMP Double Pulley – G-Rated, prusik minding, and has integrated becket for MA
- 1.5″ Single Pulley – G-Rated and lightweight with an aluminum sheave pulley
- 1.1″ Double Pulley – T-Rated, prusik minding, compact, and lightweight

Features:

- New models certified to NFPA standards including a more efficient 2″ option
- Combined swivel & pulley reduces system length, allowing more travel
- Pivoting sideplate allows rope loading without disconnecting from anchor
- Double-action detent button prevents accidental opening of the sideplate
- Sheave is mounted on sealed ball bearings for maximum efficiency
- Rotating swivel aligns rope with the direction of pull
- Swivel can be secured using rope, web, or carabiners
- Ergonomic design for anchoring and loading with one hand
- CNC machined for optimal strength & weight
- Prusik minding options facilitate progress capture
- Double sheave pulleys equipped with integrated becket
- Compatible with rope up to 13 mm (1/2 in)
- 1.5″ PMP SS Pulley is compatible with rope or wire cable
- Ideal for rescue, work at height, and tree care
- Patented, USA Made, time-tested, and proven

Printed with Pdfcrowd.com

CMC has issued a Product Recall and Safety Notice for certain lot numbers of ProSwivel Pulleys. We have corrected this issue for current and future ProSwivel Pulley production.

Option	1.1” PMP Single Swivel Pulley
Item	300434
PRODUCT WEIGHT	147 G (5.2 OZ)
PULLEY TYPE	SINGLE SHEAVE
SHEAVE MATERIAL	ALUMINUM
HEIGHT X WIDTH	112 X 51 MM (4.4 X 2.0 IN)
PULLEY COLOR	BRONZE / SLATE
NFPA RATING	TECHNICAL USE
CE STANDARDS	EN 12278
MBS	22 KN (4,946 LBF)

Option	1.1” PMP Double Swivel Pulley
Item	300433
PRODUCT WEIGHT	245 G (7 OZ)
PULLEY TYPE	DOUBLE SHEAVE
SHEAVE MATERIAL	ALUMINUM
HEIGHT X WIDTH	112 X 51 MM (4.4 X 2.0 IN)
PULLEY COLOR	BRONZE / SLATE
NFPA RATING	TECHNICAL USE
CE STANDARDS	N/A
MBS	22 KN (4,946 LBF)

Option	1.5” PMP SS Single Swivel Pulley
Item	300430
PRODUCT WEIGHT	331 G (11.7 OZ)
PULLEY TYPE	SINGLE SHEAVE
SHEAVE MATERIAL	STAINLESS STEEL
HEIGHT X WIDTH	148 X 76 MM (5.8 X 3.0 IN)
PULLEY COLOR	BRONZE / SLATE
NFPA RATING	GENERAL USE
CE STANDARDS	N/A

Printed with Pdfcrowd.com

MBS	36 KN (8,093 LBF)

Option	1.5" Single Swivel Pulley
Item	300431
PRODUCT WEIGHT	261 G (9.2 OZ)
PULLEY TYPE	SINGLE SHEAVE
SHEAVE MATERIAL	ALUMINUM
HEIGHT X WIDTH	135 X 63 MM (5.3 X 2.5 IN)
PULLEY COLOR	BRONZE / SLATE
NFPA RATING	GENERAL USE
CE STANDARDS	EN 12278
MBS	36 KN (8,093 LBF)

Option	1.5" Double Swivel Pulley
Item	300432
PRODUCT WEIGHT	415 G (14.6 OZ)
PULLEY TYPE	DOUBLE SHEAVE
SHEAVE MATERIAL	ALUMINUM
HEIGHT X WIDTH	160 X 63 MM (6.3 X 2.5 IN)
PULLEY COLOR	BRONZE / SLATE
NFPA RATING	GENERAL USE
CE STANDARDS	EN 12278
MBS	36 KN (8,093 LBF)

Option	2.0" PMP Single Swivel Pulley
Item	300437
PRODUCT WEIGHT	349 G (12.3 OZ)
PULLEY TYPE	SINGLE SHEAVE
SHEAVE MATERIAL	ALUMINUM
HEIGHT X WIDTH	148 X 76 MM (5.8 X 3.0 IN)
PULLEY COLOR	BRONZE / SLATE
NFPA RATING	GENERAL USE
CE STANDARDS	EN 12278
MBS	36 KN (8,093 LBF)

Printed with Pdfcrowd.com

Option	2.0" PMP Double Swivel Pulley
Item	300438
PRODUCT WEIGHT	585 G (20.6 OZ)
PULLEY TYPE	DOUBLE SHEAVE
SHEAVE MATERIAL	ALUMINUM
HEIGHT X WIDTH	180 X 76 MM (7.0 X 3.0 IN)
PULLEY COLOR	BRONZE / SLATE
NFPA RATING	GENERAL USE
CE STANDARDS	EN 12278
MBS	36 KN (8,093 LBF)

Option	2.6” PMP Single Swivel Pulley
Item	300436
PRODUCT WEIGHT	841 G (29.7 OZ)
PULLEY TYPE	SINGLE SHEAVE
SHEAVE MATERIAL	ALUMINUM
HEIGHT X WIDTH	191 X 93 MM (7.5 X 3.6 IN)
PULLEY COLOR	BRONZE / SLATE
NFPA RATING	GENERAL USE
CE STANDARDS	EN 12278
MBS	70 KN (15,737 LBF)

Printed with Pdfcrowd.com