SIGNALING
UL
LISTED

Sequential Activator

UL Approved

Features

- UL Compatibility Test Approval
- Up to 2 FirePro Generator units, supervised
- Extinguishing Panel, Releasing Line supervision LED
  'Fault' indicator



Description

Provides connection from the Delta FS Panel to the Aerosol Generators using four-conductor cabling. A maximum of 20 FirePro Sequential Activators can be connected to each extinguishing line.

Connect FirePro Sequential Activators to the Delta FS Releasing Fire Control Panel only.

All the following FirePro Aerosol Generator models can be connected for operation with the FirePro Sequential Activator.

Interface module			
Item No.	Product Code	Description	Size (mm)
10173	FP-SA-32G	FirePro Sequential Activator - Standard Box	97 X 97 X 48
10486	FP-SA-38G	FirePro Sequential Activator - Larger Box	186 X 132 X 50

Specification	
Construction	1.2mm mild sheet steel
Colour- lid & box	Grey BS 00 A 05 semi-matt (optional Red RAL 3002)
Operating Voltage	24VDC
Normal Standby and Alarm	1.0ma
Releasing Input	24VDC
Normal Standby	5ma
Alarm	1A Maximum
Power To Fire Single Cylinder	900ma
Cable Capacity	0.5 mm2 to 2.5 mm2
Input Delay Time	500 milliseconds +/- 100 milliseconds
Output Duration	2.1 seconds +/- 400 milliseconds

FirePro systems reserves the right to alter the specification of its products from time to time without notice. Although every effort has been made to ensure the accuracy of the information contained in this document it is not warranted or represented by FirePro systems to be a complete and up-to-date description.