

## Features:

- Four suspension wires and magnetic damping action ensure statility, even under rapidly changing atmospheric conditions, vibration, and shock.
- Excellent structure is sturdy, compact, and more tightly sealed against humidity and dust for superior performance whatever the conditions. It is quick and easy to set up, simple to sight, and immune to vibration, shock, and other environment conditions.
- The level incorporates an endless horizontal motion drive with two knobs for fast and easy aiming, operable with the right or left hand. simply turn the instrument. then use the fine motion to precisely aim the level at target.
- 5/8"X11 threads to fit standard tripod, suitable for flat and dome head tripod.

## Specification:

| Item no: | DSZ24 | DSZ32 |
|---|---|---|
| Magnification: | 24X | 32X |
| Standard deviation for 1km double run leveling | 2.0mm | 1.0mm |
| Objective aperture: | 36mm | 42mm |
| Field of view: | 1°30′ | |
| Shortest focus distance: | 0.3m | |
| Compensator type: | magnetic-damping | |
| Working range of compensator: | ±15′ | |
| Levelling accuracy: | ±0.5″ | ±0.4″ |
| Circular vial: | 8′/2mm | |
| Horizontal circle: | 360° or 400G for option | |
| Weight: | 1.6KG | |

Standard outfit: automatic level, plumb bob, adjusting wrench, instruction manual, plastic carrying case.